Configuring data source in Ushahidi V3 from the config UI

To configure data sources from the configuration's user interface(UI), you have to make sure the data_provider_config feature is enabled.

- 1. Go to WORKSPACE -> Site Settings.
- 2. Make sure data_provider_config is ticked. Otherwise tick the checkbox.
- 3. Then hit the Save Features button to enable it.

See sample screenshot of the Site Settings page.

Site Name	
testing site	
Site Owner Name	
testerbot	
	Save Site Settings
Features	
Features media_uploads sets_ui	
Features □ media_uploads □ sets_ui ☑ api_explorer	
Features media_uploads sets_ui api_explorer data_provider_config	

With the data_provider_config feature enabled, you can now configure the available data sources.

- 1. Go to WORKSPACE -> Incoming Messages -> Messages Configurations
- 2. Then select the data source you want to configure by clicking on the Configure link below the name.
- 3. Fill the data source's configuration page with the values the fields are asking for. The fields have been explained so it's easier to follow the form.
- 4. Make sure you save the changes.

To enable a data source, click on the Enable link below the name.

See sample screenshot of the Messages Configuration page.

Messages Configuration

Email

Enable SMS FrontlineSMS Disable SConfigure Nexmo Enable SConfigure

SMSSync

Disable 🕸 Configure

Twilio

Enable 📽 Configure