

Ushahidi 3.x API Config Resource

The config API endpoint is a special case. Because we're using Kohana's config classes under the hood we only really have 2 operations: get - HTTP GET - and set - HTTP PUT. You can use PUT to both create or update a config item.

- POST config
- GET config/group
 - Config group example
- GET config/group/:id
- PUT config/group/:id
- DELETE config/group/:id

POST config

The config API does not support POST.

METHOD: POST

ENDPOINT: /api/v2/config/

GET config/:group

Listing all config entries

METHOD: GET

ENDPOINT: /api/v2/config/group

AUTHENTICATED: No

Query Parameters

Name	Type	Description
group	Optional	The group name to return config entries for

Example Request

GET https://ushv3.dev/api/v2/config

Response

```
{
  "count": 4,
  "results": [[
    {
      "group_name": "site",
      "config_key": "site_name",
      "config_value": "testing site",
      "allowed_methods": {
        "get": true,
        "post": true,
        "put": true,
        "delete": true
      }
    },
    {
      "group_name": "site",
      "config_key": "owner_name",
      "config_value": "testerbot",
      "allowed_methods": {
        "get": true,
        "post": true,
        "put": true,
        "delete": true
      }
    },
    {
      "group_name": "site",
      "config_key": "site_email",
      "config_value": false,
      "allowed_methods": {
        "get": true,
        "post": true,
        "put": true,
        "delete": true
      }
    },
    {
      "group_name": "test",
      "config_key": "testkey",
      "config_value": "testval",
      "allowed_methods": {
        "get": true,
        "post": true,
        "put": true,
        "delete": true
      }
    }
  ]]
}
```

Config group example

GET https://ushv3.dev/api/v2/config/test

Response

```
{
  "count": 1,
  "results": [[
    "group_name": "test",
    "config_key": "testkey",
    "config_value": "testval",
    "allowed_methods": {
      "get": true,
      "post": true,
      "put": true,
      "delete": true
    }
  ]]
}
```

GET config/:group/:id

Get a single config entry

METHOD: GET

ENDPOINT: /api/v2/config/:group/:id

AUTHENTICATED: Yes

Query Parameters

Name	Type	Description
id	Required	The config key of the config entry
group	Required	The group name of the config entry

Example Request

GET http://ushv3.dev/api/v2/config/site/site_name

Response

```
{
  "group_name": "site",
  "config_key": "site_name",
  "config_value": "testing site",
  "allowed_methods": {
    "get": true,
    "post": true,
    "put": true,
    "delete": true
  }
}
```

PUT config/:group/:id

Update a config entry

METHOD: PUT

ENDPOINT: /api/v2/config/:group/:id

AUTHENTICATED: Yes

Query Parameters

Name	Type	Description
id	Required	The config key of the config entry being updated.
group	Required	The group name of the config entry

Example Request

PUT http://ushv3.dev/api/v2/config/site/site_name

Post Data

```
{  
  "config_value": "Updated value"  
}
```

Response

```
{  
  "group_name": "site",  
  "config_key": "test",  
  "config_value": "Updated value",  
  "allowed_methods": {  
    "get": true,  
    "post": true,  
    "put": true,  
    "delete": true  
  }  
}
```

DELETE config/:group/:id

The config API does not support DELETE.

METHOD: DELETE

ENDPOINT: /api/v2/config/:id